

Safety Data Sheet

according to ICOP 2014,2019

Issue date: 11/18/2015 Revision date: 10/4/2023 Supersedes: 12/31/2019 Version: 3.0

Danger



SECTION 1: Identification of the hazardous chemical and of the supplier

1.1. Product identifier

 Trade name
 : oxygen

 Name
 : oxygen

 CAS-No.
 : 7782-44-7

 Formula
 : O2

1.2. Other means of identification

Product code : ALM/SDS/30

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Test gas/Calibration gas.

Use for manufacture of electronic/photovoltaic components.

Laboratory use.

Industrial and professional uses. Perform risk assessment prior to use.

Contact supplier for more information on uses.

Restrictions on use : Consumer use.

1.4. Supplier details

AIR LIQUIDE MALAYSIA SDN. BHD. Lot PT 2317, No. 21, Jalan PTB 1

Kawasan Perindustrian Tangga Batu, Mukim Sungai Udang,

76400 Melaka Malaysia T +606-3513512

1.5. Emergency phone number

Emergency number : +606-3513512

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to Industry Code of Practice on chemicals classification and hazard communication (2019)

Oxidising Gases, Category 1 H270
Gases under pressure : Compressed gas H280

2.2. Label elements

Labelling according to Industry Code of Practice on chemicals classification and hazard communication (2019)

Hazard pictograms (GHS MY)





Signal word (GHS MY) : Danger

Hazard statements (GHS MY) : H270 - May cause or intensify fire; oxidizer

H280 - Contains gas under pressure; may explode if heated

Precautionary statements (GHS MY) : P220 - Keep/Store away from clothing/.../combustible materials

P244 - Keep reduction valves free from grease and oil

Safety Data Sheet

according to ICOP 2014,2019

P370+P376 - In case of fire: stop leak if safe to do so

P403 - Store in a well-ventilated place

P410+P403 - Protect from sunlight. Store in a well-ventilated place

2.3. Other hazards that do not result in classification

Other hazards which do not result in classification

: Not classified as PBT or vPvB,The substance/mixture has no endocrine disrupting

properties.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

3.1. Substances

| Name | Product identifier | % |
|--------------------|--------------------|-----|
| 1 73 | CAS-No.: 7782-44-7 | 100 |
| (Main constituent) | | |

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of necessary first aid measures

First-aid measures after inhalation : Remove victim to uncontaminated area.

First-aid measures after skin contact : Adverse effects not expected from this product.

First-aid measures after eye contact : Adverse effects not expected from this product.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms/effects, acute and delayed

 $\label{eq:most_entropy} \mbox{Most important symptoms and effects, both acute}$

and delayed

: Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness,

respiratory difficulty and convulsion. See section 11.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : None.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray or fog. Product does not burn, use fire control measures appropriate for the

surrounding fire.

Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Physicochemical hazards arising from the chemical

Reactivity in case of fire : No reactivity hazard other than the effects described in sub-sections below.

Hazardous combustion products : None.

5.3. Special protective equipment and precautions for fire fighters

Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659:

Protective gloves for firefighters. Standard EN 137 - Self-contained open-circuit compressed

air breathing apparatus with full face mask.

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat

radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems, If possible, stop flow of product, Use water spray or fog to knock down fire fumes if possible, Move containers away from the fire area if this can be

done without risk.

EAC code : 2S

10/4/2023 (Revision date) MY - en 2/9

Safety Data Sheet

according to ICOP 2014,2019

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment, and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Act in accordance with local emergency plan. Try to stop release. Evacuate area. Eliminate ignition sources. Ensure adequate air ventilation. See section 8 of the SDS for more information on personal protective equipment.

6.1.2. For emergency responders

Emergency procedures

: Monitor concentration of released product. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and materials for containment and cleaning up

Methods and material for containment and cleaning : Ventilate area.

up

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.

Safe use of the product

water into the container must be prevented. Open valve slowly to avoid pressure shock. Use no oil or grease. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not smoke while handling product. Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at http://www.eiga.eu. Use only oxygen approved lubricants and oxygen approved sealings. Avoid suck back of water, acid and alkalis. Only experienced and properly instructed persons should handle gases under pressure. Ensure the complete gas system was (or is regularily) checked for leaks before use. Use only with equipment cleaned for oxygen service and rated for container pressure. The product must be handled in accordance with good industrial hygiene and safety procedures. Consider pressure relief device(s) in gas installations. Do not breathe gas.

7.2. Conditions for safe storage, including any incompatibilities

Conditions for safe storage, including any incompatibilities

: Segregate from flammable gases and other flammable materials in store. Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

Safety Data Sheet

according to ICOP 2014,2019

SECTION 8: Exposure controls and personal protection

8.1. Control parameters

No additional information available

Exposure limit values for the other components

No additional information available

8.1.1 Biological monitoring

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Avoid oxygen rich (>23,5%) atmospheres. Gas detectors should be used when oxidising gases may be released. Provide adequate general and local exhaust ventilation. Consider the use of a work permit system e.g. for maintenance activities. Systems under pressure should be regularily checked for leakages.

8.3. Individual protection measures, such as PPE

Hand protection:

Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher.

Eye protection:

Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications

Respiratory protection:

None necessary. Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

Personal protective equipment symbol(s):





Thermal hazard protection
Environmental exposure controls

- : None in addition to the above sections.
- : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

Physical state : Gas

Appearance : No data available Colour : Colourless.
Odour : Odourless.

Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.

pH : Not applicable for gases and gas mixtures.

Melting point : -219 °C

Freezing point : No data available

Boiling point : -183 °C

Flash point : Not applicable for gases and gas mixtures.

Evaporation rate : No data available Flammability (solid, gas) : Non flammable.

Explosive limits : Upper explosion limit: Not applicable.

Lower explosion limit: Not applicable.

: Vapour pressure: Not applicable.

Vapour pressure : Vapour pressure at 50°C: Not applicable.

Vapour pressure at 50°C: Not applicable.

Safety Data Sheet

according to ICOP 2014,2019

Relative vapour density at 20°C : Not applicable.

Relative density : 1.1

Relative gas density: 1.1 Solubility : Water: 39 mg/l

Partition coefficient n-octanol/water (Log Pow) : No data available

Partition coefficient n-octanol/water (Log Kow) : Not applicable for inorganic products.

Critical temperature : -118 °C

Auto-ignition temperature : Non flammable.

Decomposition temperature : Not applicable.

Viscosity, kinematic : No reliable data available. Viscosity, dynamic : No reliable data available.

Density : Not applicable for gases and gas mixtures.

Critical pressure : 5043 kPa
Molecular mass : 32 g/mol
Oxidising properties : Oxidiser.
Ci : 1

SECTION 10: Stability and reactivity

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Violently oxidises organic material.

Conditions to avoid : Avoid moisture in installation systems.

Incompatible materials : Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 -

Cleaning of Equipment for Oxygen Service downloadable at http://www.eiga.eu,Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (> 30 bar) oxygen lines in case of combustion,May react violently with combustible materials May react violently with reducing agents For additional information or

combustible materials, May react violently with reducing agents, For additional information on compatibility refer to ISO 11114.

Hazardous decomposition products : None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified
Skin corrosion or irritation : Not classified

pH: Not applicable for gases and gas mixtures.

Serious eye damage or eye irritation : Not classified Respiratory sensitization : Not classified Skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity (STOT) – single : Not classified

exposure

Specific target organ toxicity (STOT) – repeated

exposure

: Not classified

Aspiration hazard : Not classified

oxygen (7782-44-7)

Viscosity, kinematic No reliable data available.

Other information : The substance/mixture has no endocrine disrupting properties.

Safety Data Sheet

according to ICOP 2014,2019

SECTION 12: Ecological information

12.1. Ecotoxicity

Ecology - general : No ecological damage caused by this product.

Hazardous to the aquatic environment, short-term

: Not classified

Hazardous to the aquatic environment, long-term

: Not classified

(chronic)

| oxygen (7782-44-7) | | |
|---|--|--|
| Partition coefficient n-octanol/water (Log Kow) | Not applicable for inorganic products. | |

12.2. Persistence and degradability

| oxygen (7782-44-7) | |
|-------------------------------|--|
| Persistence and degradability | No ecological damage caused by this product. |

12.3. Bioaccumulative potential

| oxygen (7782-44-7) | | |
|---|--|--|
| Partition coefficient n-octanol/water (Log Kow) | Not applicable for inorganic products. | |
| Bioaccumulative potential | No ecological damage caused by this product. | |

12.4. Mobility in soil

| oxygen (7782-44-7) | | |
|--|---|--|
| Mobility in soil No additional information available | | |
| Partition coefficient n-octanol/water (Log Kow) | n coefficient n-octanol/water (Log Kow) Not applicable for inorganic products. | |
| Ecology - soil | No ecological damage caused by this product. | |

12.5. Other adverse effects

: Not classified Effect on global warming : None.

Effect on the ozone layer : No effect on the ozone layer. Other adverse effects : No known effects from this product.

SECTION 13: Disposal information

13.1. Disposal methods

Waste treatment methods : May be vented to atmosphere in a well ventilated place. Contact supplier if guidance is

> required. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.eu for more guidance on suitable disposal methods. Do not discharge into any place where its accumulation could be dangerous. Return unused product in original

container to supplier.

Additional information : External treatment and disposal of waste should comply with applicable local and/or

national regulations.

SECTION 14: Transportation information

14.1. UN number

UN-No.(UN RTDG) : 1072 UN-No. (IMDG) : 1072 UN-No. (IATA) : 1072

14.2. UN proper shipping name

Proper Shipping Name (UN RTDG) : OXYGEN, COMPRESSED Proper Shipping Name (IMDG) : OXYGEN, COMPRESSED

10/4/2023 (Revision date) MY - en 6/9

Safety Data Sheet

according to ICOP 2014,2019

Proper Shipping Name (IATA) : Oxygen, compressed

14.3. Transport hazard class(es)

UN RTDG

Transport hazard class(es) (UN RTDG) : 2.2 (5.1) Danger labels (UN RTDG) 2.2, 5.1



IMDG

Transport hazard class(es) (IMDG) : 2.2 (5.1) Danger labels (IMDG)

2.2. 5.1



IATA

Transport hazard class(es) (IATA) : 2.2 (5.1) Danger labels (IATA) 2.2, 5.1



14.4. Packing Group, if applicable

: Not applicable Packing group (UN RTDG) Not applicable Packing group (IMDG) Packing group (IATA) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

: No supplementary information available Other information

14.6. Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

> compartment, Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, Before transporting product containers: - Ensure there is adequate ventilation, - Ensure that containers are firmly secured, - Ensure valve is closed and not leaking, - Ensure valve outlet cap nut or plug (where provided) is correctly fitted, - Ensure valve protection device (where provided) is

correctly fitted.

UN RTDG

Special provisions (UN RTDG) : 355 : 0 Limited quantities (UN RTDG) Excepted quantities (UN RTDG) : E0 Packing instruction (UN RTDG) : P200

IMDG

Special provisions (IMDG) : 355 Limited quantities (IMDG) : 0 Excepted quantities (IMDG) : E0 Packing instructions (IMDG)

: F-C - FIRE SCHEDULE Charlie - NON-FLAMMABLE GASES EmS-No. (Fire) S-W - SPILLAGE SCHEDULE Whisky - OXIDIZING GASES EmS-No. (Spillage)

Stowage category (IMDG) : A

Properties and observations (IMDG) Non-flammable, odourless gas. Strong oxidizing agent. Heavier than air (1.1).

10/4/2023 (Revision date) MY - en 7/9

Safety Data Sheet

according to ICOP 2014,2019

IATA

PCA Excepted quantities (IATA) : E0 PCA Limited quantities (IATA) : Forbidden PCA limited quantity max net quantity (IATA) : Forbidden PCA packing instructions (IATA) : 200 PCA max net quantity (IATA) : 75kg CAO packing instructions (IATA) : 200 CAO max net quantity (IATA) : 150kg Special provisions (IATA) : A175, A302 : 2X

ERG code (IATA)

14.7. Special precautions for user

IBC code : Not applicable.

14.8. Hazchem or Emergency Action Code

EAC code : 2S.

SECTION 15: Regulatory information

15.1. Safety, health, and environmental regulations specific for the hazardous chemical in question

| oxygen (7782-44-7) | | |
|--|-----------------------------------|--|
| EHS Notification and Registration Scheme | Applicable | |
| EHS Notification and Registration Scheme | Applicable | |
| Environmental Quality (Chlorofluorocarbons Prohibition) Order 1993 | Not applicable | |
| Environmental Quality (Industrial Efflluent) Regulations 2009 | | |
| Environmental Quality (Scheduled Wastes) Regulations 2007 | | |
| Control of Industrial Major Accident Hazards Regulations 1996 | Group 3 Highly reactive substance | |
| Prohibition of Use of Substance Order 1999 | Not applicable | |
| Use and Standards of Exposure of Chemical Hazardous to Health Regulations 2000 | | |
| Chemical Weapons Convention Act | | |
| Corrosive and Explosive Substances and Offensive Weapons Act | | |
| Dangerous Drugs Act | | |
| Pesticides Act | | |
| Petroleum (Safety Measures) Act | | |
| Poisons Act 1952 | | |
| Poisons (Psychotropic Substances) Regulations 1989 | | |

15.2. International agreements

No additional information available

SECTION 16: Other information

Version : 3.0 Issue date : 11/18/2015 Revision date : 04/10/2023 Supersedes : 31/12/2019

Safety Data Sheet

according to ICOP 2014,2019

Abbreviations and acronyms

: ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS# - Chemical Abstract Service number PPE - Personal Protection Equipment

LC50 - Lethal Concentration to 50 % of a test population

RMM - Risk Management Measures

PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent and Very Bioaccumulative

STOT- SE: Specific Target Organ Toxicity - Single Exposure

CSA - Chemical Safety Assessment

EN - European Standard UN - United Nations

ADR - European Agreement concerning the International Carriage of Dangerous Goods by

Road

IATA - International Air Transport Association

IMDG code - International Maritime Dangerous Goods

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

WGK - Water Hazard Class

STOT - RE: Specific Target Organ Toxicity - Repeated Exposure

UFI: Unique Formula Identifier

: Ensure operators understand the hazard of oxygen enrichment.

: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP). Key literature references and sources of data are maintained in EIGA doc 169: 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu.

Safety Data Sheet (SDS), Malaysia_AL

Training advice

Other information

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

10/4/2023 (Revision date) MY - en 9/9