

### Warning



## SECTION 1: Identification of the hazardous chemical and of the supplier

### 1.1. Product identifier

Trade name : Nitrogen (refrigerated)  
Name : Liquid Nitrogen  
CAS-No. : 7727-37-9  
Formula : N2

### 1.2. Other means of identification

Product code : ALM/SDS/92

### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Test gas/Calibration gas.  
Use for manufacture of electronic/photovoltaic components.  
Laboratory use.  
Industrial and professional uses. Perform risk assessment prior to use.  
Contact supplier for more information on uses.

Restrictions on use : Consumer use.

### 1.4. Supplier details

AIR LIQUIDE MALAYSIA SDN. BHD.  
Lot PT 2317, No. 21, Jalan PTB 1  
Kawasan Perindustrian Tangga Batu, Mukim Sungai Udang,  
76400 Melaka  
Malaysia  
T +606-3513512

### 1.5. Emergency phone number

Emergency number : +606-3513512

## SECTION 2: Hazards identification

### 2.1. Classification of the hazardous chemical

Classification according to Industry Code of Practice on chemicals classification and hazard communication (2019)

Gases under pressure : Refrigerated liquefied gas H281

### 2.2. Label elements

Labelling according to Industry Code of Practice on chemicals classification and hazard communication (2019)

Hazard pictograms (GHS MY) :



Signal word (GHS MY) : Warning  
Hazard statements (GHS MY) : H281 - Contains refrigerated gas; may cause cryogenic burns or injury  
Precautionary statements (GHS MY) : P282 - Wear cold insulating gloves/face shield/eye protection  
P315 - Get immediate medical advice/attention  
P336 - Thaw frosted parts with lukewarm water. Do no rub affected area  
P403 - Store in a well-ventilated place

# Nitrogen (refrigerated)

## Safety Data Sheet

according to ICOP 2014,2019

### 2.3. Other hazards that do not result in classification

Other hazards which do not result in classification : Asphyxiant in high concentrations.

## SECTION 3: Composition and information of the ingredients of the hazardous chemical

### 3.1. Substances

Name	Product identifier	%
Liquid Nitrogen (Main constituent)	CAS-No.: 7727-37-9	100

Full text of H-statements: see section 16

### 3.2. Mixtures

Not applicable

## SECTION 4: First-aid measures

### 4.1. Description of necessary first aid measures

First-aid measures after inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
First-aid measures after skin contact	: In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes.
First-aid measures after ingestion	: Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms/effects, acute and delayed

Most important symptoms and effects, both acute and delayed : In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : None.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

Suitable extinguishing media : Water spray or fog.  
Unsuitable extinguishing media : Do not use water jet to extinguish.

### 5.2. Physicochemical hazards arising from the chemical

Reactivity in case of fire : No reactivity hazard other than the effects described in sub-sections below.  
Hazardous combustion products : None.

### 5.3. Special protective equipment and precautions for fire fighters

Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

Specific methods : If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire, Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems, If possible, stop flow of product, Use water spray or fog to knock down fire fumes if possible, Move containers away from the fire area if this can be done without risk.

EAC code : 2T

# Nitrogen (refrigerated)

## Safety Data Sheet

according to ICOP 2014,2019

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment, and emergency procedures

General measures : Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Oxygen detectors should be used when asphyxiating gases may be released. Use protective clothing. Act in accordance with local emergency plan. Stay upwind.

##### **6.1.1. For non-emergency personnel**

Emergency procedures : Act in accordance with local emergency plan. Try to stop release. Evacuate area. Ensure adequate air ventilation. Use protective clothing. Stay upwind. See section 8 of the SDS for more information on personal protective equipment.

##### **6.1.2. For emergency responders**

Emergency procedures : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Oxygen detectors should be used when asphyxiating gases may be released. See section 5.3 of the SDS for more information.

#### 6.2. Environmental precautions

Try to stop release. Liquid spillages can cause embrittlement of structural materials.

#### 6.3. Methods and materials for containment and cleaning up

Methods and material for containment and cleaning up : Ventilate area.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Safe handling of the gas receptacle : Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.

Safe use of the product : The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis. Do not breathe gas. Avoid release of product into work area.

#### 7.2. Conditions for safe storage, including any incompatibilities

Conditions for safe storage, including any incompatibilities : Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.

# Nitrogen (refrigerated)

## Safety Data Sheet

according to ICOP 2014,2019

### SECTION 8: Exposure controls and personal protection

#### 8.1. Control parameters

No additional information available

#### Exposure limit values for the other components

No additional information available

#### 8.1.1 Biological monitoring

No additional information available

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Consider the use of a work permit system e.g. for maintenance activities.

#### 8.3. Individual protection measures, such as PPE

##### Hand protection:

Wear cold insulating gloves when transfilling or breaking transfer connections. Standard EN 511 - Cold insulating gloves. Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher.

##### Eye protection:

Wear goggles and a face shield when transfilling or breaking transfer connections. Standard EN 166 - Personal eye-protection - specifications

##### Respiratory protection:

Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

#### Personal protective equipment symbol(s):



Thermal hazard protection : None in addition to the above sections.  
Environmental exposure controls : None necessary.

### SECTION 9: Physical and chemical properties

Physical state : Gas  
Appearance : No data available  
Colour : Colourless liquid.  
Odour : No odour warning properties.  
Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure.  
pH : Not applicable for gases and gas mixtures.  
Melting point : -210 °C  
Freezing point : No data available  
Boiling point : -196 °C  
Flash point : Not applicable for gases and gas mixtures.  
Evaporation rate : No data available  
Flammability (solid, gas) : Non flammable.  
Explosive limits : Upper explosion limit: Not applicable.  
Lower explosion limit: Not applicable.  
Vapour pressure : Vapour pressure: Not applicable.  
Vapour pressure at 50°C: Not applicable.

# Nitrogen (refrigerated)

## Safety Data Sheet

according to ICOP 2014,2019

Relative vapour density at 20°C	: Not applicable.
Relative density	: 0.8 Relative gas density: 0.97
Solubility	: Water: 20 mg/l
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Critical temperature	: -147 °C
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: No reliable data available.
Viscosity, dynamic	: No reliable data available.
Explosive properties	: Not applicable.
Density	: Not applicable for gases and gas mixtures.
Critical pressure	: 3390 kPa
Molecular mass	: 28 g/mol
Oxidising properties	: Not applicable.

### SECTION 10: Stability and reactivity

Reactivity	: No reactivity hazard other than the effects described in sub-sections below.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: None.
Conditions to avoid	: Avoid moisture in installation systems.
Incompatible materials	: Materials such as carbon steel, low alloy carbon steel and plastic become brittle at low temperatures and are subject to failure. Use appropriate materials compatible with the cryogenic conditions present in refrigerated liquefied gas systems, For additional information on compatibility refer to ISO 11114.
Hazardous decomposition products	: None.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion or irritation	: Not classified pH: Not applicable for gases and gas mixtures.
Serious eye damage or eye irritation	: Not classified
Respiratory sensitization	: Not classified
Skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (STOT) – single exposure	: Not classified
Specific target organ toxicity (STOT) – repeated exposure	: Not classified
Aspiration hazard	: Not classified

#### Nitrogen (refrigerated) (7727-37-9)

Viscosity, kinematic	No reliable data available.
----------------------	-----------------------------

Other information : The substance/mixture has no endocrine disrupting properties.

### SECTION 12: Ecological information

#### 12.1. Ecotoxicity

Ecology - general : No ecological damage caused by this product.

# Nitrogen (refrigerated)

## Safety Data Sheet

according to ICOP 2014,2019

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Nitrogen (refrigerated) (7727-37-9)	
Partition coefficient n-octanol/water (Log Kow)	Not applicable for inorganic products.

### 12.2. Persistence and degradability

Nitrogen (refrigerated) (7727-37-9)	
Persistence and degradability	No ecological damage caused by this product.

### 12.3. Bioaccumulative potential

Nitrogen (refrigerated) (7727-37-9)	
Partition coefficient n-octanol/water (Log Kow)	Not applicable for inorganic products.
Bioaccumulative potential	No data available.

### 12.4. Mobility in soil

Nitrogen (refrigerated) (7727-37-9)	
Mobility in soil	No additional information available
Partition coefficient n-octanol/water (Log Kow)	Not applicable for inorganic products.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.

### 12.5. Other adverse effects

Ozone : Not classified  
Effect on global warming : None.  
Effect on the ozone layer : None.  
Other adverse effects : Can cause frost damage to vegetation.

## SECTION 13: Disposal information

### 13.1. Disposal methods

Waste treatment methods : May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous. Return unused product in original container to supplier.

Additional information : External treatment and disposal of waste should comply with applicable local and/or national regulations.

## SECTION 14: Transportation information

### 14.1. UN number

UN-No.(UN RTDG) : 1977  
UN-No. (IMDG) : 1977  
UN-No. (IATA) : 1977

### 14.2. UN proper shipping name

Proper Shipping Name (UN RTDG) : NITROGEN, REFRIGERATED LIQUID  
Proper Shipping Name (IMDG) : NITROGEN, REFRIGERATED LIQUID  
Proper Shipping Name (IATA) : Nitrogen, refrigerated liquid

### 14.3. Transport hazard class(es)

#### UN RTDG

Transport hazard class(es) (UN RTDG) : 2.2  
Danger labels (UN RTDG) : 2.2

# Nitrogen (refrigerated)

## Safety Data Sheet

according to ICOP 2014,2019



### IMDG

Transport hazard class(es) (IMDG) : 2.2  
Danger labels (IMDG) : 2.2



### IATA

Transport hazard class(es) (IATA) : 2.2  
Danger labels (IATA) : 2.2



### 14.4. Packing Group, if applicable

Packing group (UN RTDG) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Dangerous for the environment : No  
Marine pollutant : No  
Other information : No supplementary information available

### 14.6. Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment, Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency, Before transporting product containers: - Ensure there is adequate ventilation, - Ensure that containers are firmly secured, - Ensure valve is closed and not leaking, - Ensure valve outlet cap nut or plug (where provided) is correctly fitted, - Ensure valve protection device (where provided) is correctly fitted.

### UN RTDG

Special provisions (UN RTDG) : 345, 346  
Limited quantities (UN RTDG) : 120 ml  
Excepted quantities (UN RTDG) : E1  
Packing instruction (UN RTDG) : P203  
Portable tank and bulk container special instructions (UN RTDG) : T75  
Portable tank and bulk container special provisions (UN RTDG) : TP5

### IMDG

Special provisions (IMDG) : 345, 346  
Limited quantities (IMDG) : 120 ml  
Excepted quantities (IMDG) : E1  
Packing instructions (IMDG) : P203  
Tank instructions (IMDG) : T75  
Tank special provisions (IMDG) : TP5  
EmS-No. (Fire) : F-C - FIRE SCHEDULE Charlie - NON-FLAMMABLE GASES  
EmS-No. (Spillage) : S-V - SPILLAGE SCHEDULE Victor - GASES (NON-FLAMMABLE, NON-TOXIC)  
Stowage category (IMDG) : D

# Nitrogen (refrigerated)

## Safety Data Sheet

according to ICOP 2014,2019

Properties and observations (IMDG) : Liquefied, non-flammable, odourless gas. Lighter than air (0.97). Arrangements for the containment of the liquid nitrogen and fittings in use should be appropriate to the potential danger to the structure of the freight container or ship from the effect of misuse or accidental spillage.

### IATA

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Forbidden  
PCA limited quantity max net quantity (IATA) : Forbidden  
PCA packing instructions (IATA) : 202  
PCA max net quantity (IATA) : 50kg  
CAO packing instructions (IATA) : 202  
CAO max net quantity (IATA) : 500kg  
Special provisions (IATA) : A152  
ERG code (IATA) : 2L

### 14.7. Special precautions for user

IBC code : Not applicable.

### 14.8. Hazchem or Emergency Action Code

EAC code : 2T.

## SECTION 15: Regulatory information

### 15.1. Safety, health, and environmental regulations specific for the hazardous chemical in question

<b>Nitrogen (refrigerated) (7727-37-9)</b>	
EHS Notification and Registration Scheme	Not applicable
EHS Notification and Registration Scheme	Not applicable
Environmental Quality (Chlorofluorocarbons Prohibition) Order 1993	
Environmental Quality (Industrial Effluent) Regulations 2009	
Environmental Quality (Scheduled Wastes) Regulations 2007	
Control of Industrial Major Accident Hazards Regulations 1996	
Prohibition of Use of Substance Order 1999	
Use and Standards of Exposure of Chemical Hazardous to Health Regulations 2000	
Chemical Weapons Convention Act	
Corrosive and Explosive Substances and Offensive Weapons Act	
Dangerous Drugs Act	
Pesticides Act	List of active ingredients
Petroleum (Safety Measures) Act	Not applicable
Poisons Act 1952	
Poisons (Psychotropic Substances) Regulations 1989	

### 15.2. International agreements

No additional information available

## SECTION 16: Other information

Version : 3.0  
Issue date : 3/25/2015  
Revision date : 03/04/2024  
Supersedes : 25/02/2020



# Nitrogen (refrigerated)

## Safety Data Sheet

according to ICOP 2014,2019

---

### Abbreviations and acronyms

- : ATE - Acute Toxicity Estimate
  - CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
  - REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
  - EINECS - European Inventory of Existing Commercial Chemical Substances
  - CAS# - Chemical Abstract Service number
  - PPE - Personal Protection Equipment
  - LC50 - Lethal Concentration to 50 % of a test population
  - RMM - Risk Management Measures
  - PBT - Persistent, Bioaccumulative and Toxic
  - vPvB - Very Persistent and Very Bioaccumulative
  - STOT- SE : Specific Target Organ Toxicity - Single Exposure
  - CSA - Chemical Safety Assessment
  - EN - European Standard
  - UN - United Nations
  - ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
  - IATA - International Air Transport Association
  - IMDG code - International Maritime Dangerous Goods
  - RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
  - WGK - Water Hazard Class
  - STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
- Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Safety Data Sheet (SDS), Malaysia\_AL

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.